



BLEED VALVES


- ◆ Working pressure up to 10,000 psig (690 bar)
- ◆ Working temperature: -65°F to 850°F (-54 °C to 454 °C)
- ◆ Compact design for convenient installation
- ◆ End connection: 1/8" to 1/2" pipe thread



Type 1



Type 2



Type 3

订购型号说明

A B C D E F G H
SS - DV - N4 -L-C -S -W

A	阀体材料
SS	316 SS
4S	304 SS
21S	321 SS
904L	904L SS
6L	316L SS
B	Brass

B	Series
DV	DV Series

C	Inlet Type
N	Male NPT
RT	Male BSPT

D	Inlet Size
2	1/8"
4	1/4"
6	3/8"
8	1/2"

E	Vent
	Default=Type1
L	Type2
T	Type3

F	Handle
NO	Type1
C	StainlessSteel Handle (for Type 2.and Type 3)

G	Special Application
	Default=NO
S	NACE MR 0175

H	Cleaning and Packaging
	Default = Standard cleaning and packaging for general industrial use
W	Degreasing
W2	Oxygen-rich cleaning

RELIEF VALVES



UV Series

- ◆ Set Pressure 7 color-coded springs available for wide range of set pressure, 50 to 6000 psig @ 70°F (3.4 to 414 bar @ 20°C)
- ◆ Orifice size: 0.14" (3.6mm)
- ◆ Working temperature: -40°F to 300°F (-40°C to 148°C)
- ◆ Maximum outlet pressures: 1500 psig (103 bar)
- ◆ Variety of end connections available
- ◆ Liquid or gas service
- ◆ End connections: 1/4" to 3/4" thread

1/4" to 3/4" Tube Fitting
 6mm to 18mm Tube Fitting

UW Series

- ◆ Set Pressure 10 to 150 psig @ 70°F (0.68 to 10.3 bar @ 20°C)
- ◆ Maximum outlet pressure: 150 psig (10.3 bar)
- ◆ Orifice size: 0.19" (4.8mm), 0.25" (6.4 mm)
- ◆ Working temperature: -40°F to 300°F (-40°C to 148°C)
- ◆ Maximum outlet pressures: 150psig(10.3bar)
- ◆ Variety of end connections available
- ◆ Liquid or gas service
- ◆ End connections: 1/4" to 3/4" thread

1/4" to 3/4" Tube Fitting
 6mm to 18mm Tube Fitting

