



Серии до 3 000 psi (207 атм)

QC, QF, QV, QM and QTM Series

Производство Китай



Информация для заказа:

SS - QC4 - FL4 - S - K1 - B - CE

Material	Series	End Connection Type	End Connection Size	Stem or Body	Key Number and Color	O-ring Material	Special Application
SS 316 SS	QC4 1/4" (6.4 mm)	FNS Female NPT	4 1/4"	S Stem without valve remains open when uncoupled	Without key	Fluorocarbon FKM	NO
B Brass	QC6 3/8" (9.5 mm)	NS Male NPT	6 3/8" or 6 mm	D Stem with valve shuts off when uncoupled	K1 Black	B Buna N	CE NACE MR 0175
	QC8 1/2" (12.7 mm)	FRT Female BSPT	8 1/2" or 8 mm	B Body with valve shuts off when uncoupled	K2 Orange	E EPDM	
		RT Male BSPT	10 5/8" or 10 mm	F Full-flow body	K3 Green	N Neoprene	
		FMS Female Metric Thread (for RG gasket)	12 3/4" or 12 mm		K4 Yellow	Z Kalrez	
		MS Male Metric Thread (for RG gasket)	14 M14 x 1.5		K5 Blue		
		FL Fractional Tube Fitting	16 1" or 16 mm		K6 White		
		ML Metric Tube Fitting	18 M18 x 1.5		K7 Purple		
		FT Fractional Tube Adapter	20 M20 x 1.5		K8 Brown		
		MT Metric Tube Adapter					
		AN Male JIC 37° Flare					

- Подробные каталоги с техническими характеристиками предоставляются по запросу