



Производство Китай

Информация для заказа:

20 Series Tubing

- ⊙ Working pressure: 20000 psig (1379 bar).
- ⊙ 316 and 304 stainless steel are standard materials. Other materials are available upon request.
- ⊙ Material, size and heat code are indicated on the tubing surface.

T - Tube O.D. in.	Tx - Tube I.D. in.	Material	Basic Ordering Number	Tolerance O.D. in. (mm)
1/4	0.109	316 SS	SS-MT-2FH4-	0.248/0.243 (6.30/6.17)
1/4	0.109	304 SS	S4-MT-2FH4-	0.248/0.243 (6.30/6.17)
3/8	0.203	316 SS	SS-MT-2FH6-	0.370/0.365 (9.40/9.27)
3/8	0.203	304 SS	S4-MT-2FH6-	0.370/0.365 (9.40/9.27)
9/16	0.312	316 SS	SS-MT-2FH9-	0.557/0.552 (14.15/14.02)
9/16	0.312	304 SS	S4-MT-2FH9-	0.557/0.552 (14.15/14.02)
3/4	0.438	316 SS	SS-MT-2FH12-	0.745/0.740 (18.92/18.80)
3/4	0.438	304 SS	S4-MT-2FH12-	0.745/0.740 (18.92/18.80)
1	0.562	316 SS	SS-MT-2FH16-	0.995/0.990 (25.27/25.14)
1	0.562	304 SS	S4-MT-2FH16-	0.995/0.990 (25.27/25.14)



60 Series Tubing

- ⊙ Working pressure: 60000 psig (4137 bar).
- ⊙ 316 and 304 stainless steel are standard materials. Other materials are available upon request.
- ⊙ Material, size and heat code are indicated on the tubing surface.

T - Tube O.D. in.	Tx - Tube I.D. in.	Material	Basic Ordering Number	Tolerance O.D. in. (mm)
1/4	0.083	316 SS	SS-HT-6FH4-	0.248/0.243 (6.30/6.17)
1/4	0.083	304 SS	S4-HT-6FH4-	0.248/0.243 (6.30/6.17)
3/8	0.125	316 SS	SS-HT-6FH6-	0.370/0.365 (9.40/9.27)
3/8	0.125	304 SS	S4-HT-6FH6-	0.370/0.365 (9.40/9.27)
9/16	0.188	316 SS	SS-HT-6FH9-	0.557/0.552 (14.15/14.02)
9/16	0.188	304 SS	S4-HT-6FH9-	0.557/0.552 (14.15/14.02)



- Подробные каталоги с техническими характеристиками предоставляются по запросу